hi-view
High Resolution High Technology

HI-6110V

Main Feature

1/3" SONY CCD Sensor, 650 TV line,
Lux 0.2/F2.0, 4~9mm Vari-Folcal Lens,
ATW,BLC more than 48 dB, Power DC 12 V.

Specification

Model	HI-6110V
Image Device	1/3" SONY CCD Sensor
Scanning Frequency	NTSC: 15,734KHz(H), 60Hz(V); PAL: 15,625KHz(H),50Hz(V)
Scanning System	NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace
Effective Pixels	NTSC: 811(H) X 508(V); PAL: 795(H) X 596(V);
Electronic Shutter	N:1/60- 1/100,000 sec (Auto); PAL:1/50-1/100,000sec (Auto)
Horizontal	650 TV Lines
White-balance	Auto white balance (2500 ˚K~9500 ˚K)
Synchronizing System	Internal
Sensitivity	0.2 Lux / F2.0
BLC	Auto
Signal to Noise	More than 48dB AGC off
AGC	Yes
Gamma Correction	0.45
Lens	Vari-Folcal Lens 4~9mm
Power Consumption	120mA, -+ 5mA
Power Supply	DC 12 V
Temperature	Operating: -10 to 50 ˚C
Video Output	Composite 1.0 Vp-p at 75 ohm
Contruction	Aluminium
Dimension	86(O) x 64(H) mm
Weight	500 G

*ทางบริษัทขอสงวนสิทธิ์ในการเปลี่ยนแปลง แก้ไข โดยไม่แจ้งให้ทราบล่วงหน้า